

3. SPOJNI PRIBOR General hardware

3.9. Zatvarači

Zatvarač užni za zalijevanje OSS

Open spelter socket

Min. prekidna sila (Mt)	Za užu promjera Ø (mm)	Strukturalni struk Ø (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Ø H (mm)	Ø K (mm)	Ø P (mm)	Težina (kg/kom)
MBL	For rope dia.	Structural strand Ø	Weight										
8	6-7	-	105	46	40	19	34	9	18	10	20	17,5	0,4
12	8-10	-	122	54	45	23	40	11,2	20,6	13,5	26	20,6	0,8
20	11-13	-	142	64	51	27	48	12,7	25,6	15	30	25,4	1,1
25	14-16	12-13	171	76	63	32	56	14,5	32	18,5	38,5	30	1,9
40	18-19	14-16	205	89	76	40	68	16,5	38	22,5	46	35	3,2
55	20-22	18-19	238	101	89	48	80	20,5	45	26,8	55	41	5,3
80	23-26	20-22	273	114	101	58	98	22,5	51	29,5	62	51	8,4
100	27-30	24-26	306	127	114	65	110	25	57	34	70	57	11,3
130	31-36	27-28	338	139	127	72	124	28	63	40	83	63	16
160	37-39	30-32	394	152	162	80	140	30	76	44,5	90	70	23
200	40-42	33-35	415	165	165	85	148	33,5	76	48	97	76	29
250	43-48	36-40	467	191	178	98	170	39	89	53	112	89	43
300	49-54	42-45	552	216	228	108	186	46	101	58,5	125	95	64
375	55-60	46-48	603	229	254	120	210	53	113	68,5	135	108	85
450	61-68	50-54	654	248	273	133	230	60	127	77,5	150	121	119
500	69-75	56-62	696	279	279	138	240	73	133	83	160	127	158
600	76-80	64-67	736	305	286	145	250	76	146	89	170	133	186
650	81-86	70-73	790	330	300	160	275	79	159	95	180	140	227
750	87-93	76-80	849	356	318	175	300	82	172	99	200	152	280
900	94-102	83-92	922	381	343	198	336	89	191	110	215	178	375
1200	108-115	96-108	1110	440	450	220	370	100	205	128	250	195	525
1400	120-128	112-121	1185	490	440	255	430	113	225	143	270	220	680

2.1 2.2 CE

