

## 3. SPOJNI PRIBOR General hardware



### 3.9. Zatvarači

#### Užni zatvarač G-6413 Green Pin

##### Open wedge socket G-6413

2.1 2.2 CE 

Broj	Min prekidna sila (t)	Promjer užeta (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Težina (kg/kom)
No.	MBL	Rope dia.								Weight
0.25	8	7-8	128	110	51	18	16	9	36	0,8
0.5	12	9-10	165	142	62	20,5	21	11	46	1,5
1	20	11-13	175	146	66	25	25	12	57	2,4
2	25	14-16	211	176	82	31	30	15	70	4
3	40	18-19	252	212	95	38	35	16	80	7
4	55	20-22	288	240	110	44	41	19	95	11
5	75	24-26	329	274	130	51	51	22	110	16
6	90	27-29	375	310	145	57	57	25	130	22
7	110	30-32	423	350	155	63	64	28	146	31
8	125	34-36	474	400	163	69	64	28	148	39
9	150	37-39	527	450	178	76	70	30	153	48
10	170	40-42	580	500	187	76	76	33	160	64
11	225	43-48	650	550	226	89	89	39	186	96
12	280	49-52	745	640	257	101	95	46	194	130
13	360	54-58	785	660	275	114	108	54	230	180
14	425	60-68	970	835	300	127	121	60	250	275
15	460	72-76	1150	1000	355	146	133	76	270	440
16	625	81-86	1252	1100	375	159	140	79	300	510




- EN 13411-6
- materijal: visokootporni čelik
- završna obrada: vruće cinčani

#### Užni zatvarač sa osiguračem i maticom G-6423 Green Pin

##### Open wedge socket with safety pin G-6423

2.1 2.2 CE 

Broj	Min. prekidna sila (t)	Promjer užeta (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Težina (kg/kom)
No.										Weight
0,25	8	7-8	128	110	69	18	16	9	36	0,8
0,5	12	9-10	165	142	83	20,5	20	11	46	1,5
1	20	11-13	175	146	101	25	25	12	57	2,4
2	25	14-16	211	176	124	31	30	15	70	4,8
3	40	18-19	252	212	138	38	35	16	80	8,3
4	55	20-22	288	240	148	44	41	19	95	11
5	75	24-26	329	274	176	51	50	22	110	17,9
6	90	27-29	375	310	193	57	57	25	130	21
7	110	30-32	423	350	210	63	63	28	146	33
8	125	34-36	474	400	216	69	65	28	148	42
9	150	37-39	527	450	230	76	70	30	153	53
10	170	40-42	580	500	244	76	77	33	160	73



- EN 13411-6
- materijal: visokootporni čelik
- završna obrada: vruće cinčani