

# 1. ČELIČNA UŽAD I LANCI Wire ropes and chains


## 1.2. Opća namjena

Čelično užje: 6x36WS + vlaknasta jezgra

Wire rope: 6x36WS+ FC

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm <sup>2</sup>	Min. prekidna sila (kN) 1960 N/mm <sup>2</sup>	Težina (kg/100 m)
Diameter	MBL	Weight	MBL
8	37,40	41,4	23,50
9	47,30	52,40	29,7
10	58,4	64,7	36,7
11	70,70	78,30	44,4
12	84,1	93,10	52,8
13	98,7	109,0	62,0
14	114,0	127,0	71,9
16	150,0	166,0	94,0
18	189,0	210,0	119,0
20	234,0	259,0	147,0
22	283,0	313,0	178,0
24	336,0	373,0	211,0
26	395,0	437,0	248,0
28	458,0	507,0	288,0
30	526,0	582,0	330,0
32	598,0	662,0	376,0
36	757,0	838,0	476,0
38	843,0	934,0	530,0
40	935,0	1040,0	587,0
44	1130,0	1250,0	711,0
48	1350,0	1490,0	846,0
52	1580,0	1750,0	992,0
56	1830,0	2030,0	1150,0
60	2100,0	2330,0	1320,0



- EN 12385-4
- DIN 3064
- završna obrada: crno, el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm<sup>2</sup> ili 1960 N/mm<sup>2</sup>

