

5. DIZALICE, KOLICA I HVATALJKE Hoists, clamps

5.1. Dizalice lančane ručne


Dizalica lančana ručna antikoroziivna za marine RX-lift

Manual anti-corosion chain hoist RX-lift




- EN 13157
- za sigurno i jednostavno korištenje pri uvjetima velikih saliniteta
- primjereno za marine u okruženju visokog saliniteta
- dizalica sa posebnom anti-koroziivnom zaštitom prema ISO 12944 standardu: do najvećeg razreda C5-M
- mogućnost: lanac od nehrđajućeg čelika
- limitator tereta - opcionalan


2.1 2.2 CE MTCa MTCb




0,25t-3,0t



3,0t-5,0t



7,5t-15,0t



20,0t-30,0t

Kapacitet (t) Capacity	0,5	1	1,5	2	3	5	10	15	20
Veličine nosivog lanca (mm) Load chain dimension	5x15	6x18	7x21	8x24	10x30	10x30	10x30	10x30	10x30
A (mm)	148	172	196	210	255	280	385	405	640
B min. (mm)	132	151	173	175	205	189	189	242	226
C (mm)	23	26	29,5	34	39	41	50	80	80
D (mm)	35	40	45	50	55	65	85	110	110
Hmin (mm)	345	376	442	470	580	690	780	920	980
Neto težina (kg) Net weight	9,3	12,2	16,5	19,5	320	43	80,7	140	180


Dizalica ručna lančana neiskreća ATEX RX-lift

Spark proof manual chain hoist ATEX RX-lift




- dizalica u skladu sa EU standardom ATEX 2014/34/EU i Direktivi 2006/42/EC, CE/ GS
- razina otpornosti zaštite od eksplozije: Ex II 2 GD c II II C T4 IIIC T135
- prikladno za: potencijalno eksplozivnu ili prašnju atmosferu
- područja rada: Zona 1 i 2 (plin), Zona 21 i 22 (prašina)
- cijeli proizvod opremljen je anti-iskrećim omotačem, a sustav kočnice u potpunosti štiti stranu tvar od ulaska u mehanizam
- nosivi lanac: pocinčani ili od nehrđajućeg čelika


2.1 2.2 CE MTCa MTCb




0,25t-3,0t



3,0t-5,0t



7,5t-15,0t



20,0t-30,0t

Kapacitet (t) Capacity	0,5	1,0	2,0	3,0	5,0	10,0	15,0	20,0
Broj pada lanca Strands of load chain	1	1	1	1	2	4	6	8
Dimenzije nosivog lanca (mm) Load chain dimension	5x15	6x18	8x24	10x30	10x30	10x30	10x30	10x30
A (mm)	148	172	210	255	280	385	405	640
B (mm)	132	151	175	205	189	189	242	226
C (mm)	23	26	34	39	41	50	80	80
D (mm)	35	40	50	55	65	85	110	110
H min. (mm)	348	376	470	580	690	780	920	980
Neto težina (kg) Net weight	9,3	12,2	19,5	32	43	80,7	140	180