

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.3. Nerotirajuće uže

Čelično uže: 35W×K7+čelična jezgra KOMPAKTNO

Wire rope: 35Wx7+IWRC non-rotating, compacted

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 2160 N/mm ²	Težina (kg/100m)
Diameter	MBL	Weight
10	96	48
11	116	58
12	138	68
13	162	81
14	188	94
15	216	108
16	245	122
17	277	138
18	311	155
19	346	173
20	372	195
21	424	215
22	474	241
23	519	267
24	551	284
25	606	312
26	652	335
27	700	360
28	760	391
29	803	413
30	866	446
31	929	478
32	977	503
33	1032	536
34	1105	574
35	1166	606
36	1235	642
37	1296	674
38	1381	718
39	1449	753
40	1525	793
41	1954	828
42	1673	870
43	1756	913
44	1825	948
45	1912	993
46	2007	1040
47	2086	1080
48	2186	1140



- EN 12385-4
- DIN 3072
- završna obrada: crno, el. galvanizirano ili vruće cinkano
- čvrstoća žice: 1960 N/mm² ili 2160 N/mm²

