


6. EL. DIZALICE, VITLA I VILIČARI El. hoists, forklifts

6.1. Električne dizalice i vitla

Kranska vaga tip OCS-A RX-lift

Crane scale type OCS RX-lift

Max. kapacitet (kg)	A (mm)	B (mm)	C (mm)	L (mm)	Neto težina (kg)
Max. Capacity					N.W.
1000	58	83	30	420	13
2000	58	83	30	420	13
3000	73	107	33	480	16
5000	92	135	45	585	25
10000	94	145	60	770	47
15000	125	178	75	860	64
20000	135	250	75	950	68



2.1 2.2 CE

* tip A- fiksna kuka

* tip B- okretna kuka

- razred točnosti: OIML III
- nultl raspon 4% F.S.
- osiguranje od preopterećenja: <125% F.S.
- alarm preopterećenja: 100 F.S. +9e
- baterija: 6V/10Ah baterija sa mogućnošću punjenja
- radni vijek baterije: ≥100h
- radna temperatura -10°C do +40°C
- maks. udaljenost daljinskog ≥10m

Dinamometar tip CS-14 RX-lift

Dynamometer type CS-14 RX-lift

Max. kapacitet (kg)	Min. kapacitet (kg)	Razred (kg)	Broj
Max. Capacity	Min. Capacity	Grade	Number
1000	10	0,5	2000
2000	20	1,0	2000
3000	20	1,0	3000
5000	40	2,0	2500
10000	100	5,0	2000
15000	100	5,0	3000
20000	200	10,0	2000
30000	200	10,0	3000
50000	400	20,0	2500



2.1 2.2 CE

- integrirana struktura
- 22 mm LCD ekran
- 3 x AA baterije
- vodootporna ploča