

# 1. ČELIČNA UŽAD I LANCI Wire ropes and chains


## 1.3. Nerotirajuće uže

### Čelično uže: 8 DURA PLUS 8P

#### Wire rope: 8 DURA PLUS 8P

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm <sup>2</sup>	Min. prekidna sila (kN) 1960 N/mm <sup>2</sup>	Težina (kg/100m)
Diameter	MBL	MBL	Weight
8	47,4	51,0	26
9	59,9	65,0	33
9,5	66,8	72,4	37
10	74,0	80,0	42
11	89,5	96,0	51
12	107,0	118,0	61
12,7	119,0	129,0	68
13	125,0	138,0	72
14	145,0	160,0	84
14,3	151,0	167,0	88
15	167,0	180,0	96
16	189,0	209,0	112
17	214,0	236,0	126
18	240,0	265,0	140
19	267,0	293,0	155
20	296,0	325,0	174
21	326,0	358,0	192
22	358,0	393,0	210
23	391,0	430,0	230
24	426,0	468,0	248
25	463,0	492,0	269
25,4	477,0	507,0	279
26	500,0	555,0	290
27	539,0	599,0	313
28	580,0	638,0	342
28,6	605,0	666,0	354
29	622,0	685,0	364
30	666,0	737,0	390
31	711,0	787,0	416
32	758,0	837,0	440
33	806,0	890,0	468
34	855,0	945,0	496
35	907,0	1000,0	533
36	959,0	1054,0	560
38	1069,0	1180,0	623
40	1184,0	1308,0	690
41,3	1262,0	1394,0	736
42,0	1305,0	1445,0	766
44	1433,0	1580,0	836
46	1566,0	1723,0	986
48	1705,0	1880,0	1010
50	1850,0	2040,0	1100



- EN 12385-4
- nerotirajuće, vrlo savitljivo uže
- završna obrada: crno, el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm<sup>2</sup> ili 1960 N/mm<sup>2</sup>

