

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.2. Opća namjena

Čelično užje: 6x7+ vlaknasta jezgra

Wire rope: 6x7+ FC

Promjer (mm) Diameter	Min. prekidna sila (kN) 1770 N/mm ² MBL	Težina (kg/ 100 m) Weight
2	2.35	1.38
3	5.29	3.11
4	9.40	5.52
5	14.70	8.63
6	21.20	12.40
7	28.80	16.90
8	37.60	22.10
9	47.60	27.90
10	58.80	34.50
11	71.10	41.70
12	84.60	49.70
13	99.30	58.30
14	115.00	67.60
16	150.00	88.30
18	190.00	112.00
20	235.00	138.00

CE 2.1 2.2 3.1 BL




- EN 12385-4
- DIN 3055
- završna obrada: el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm²

Čelično užje: 6x7 + čelična jezgra

Wire rope: 6x7 + IWRC

Promjer (mm) Diameter	Min. prekidna sila (kN) 1770 N/mm ² MBL	Težina (kg/ 100 m) Weight
2	2,54	1,54
3	5,72	3,46
4	10,20	6,14
5	15,90	9,60
6	22,90	13,80
7	31,10	18,80
8	40,70	24,6
9	51,50	31,1
10	63,5	38,4
11	76,90	46,5
12	91,50	55,30
13	107,0	64,9
14	125,0	75,30
16	163,0	98,3
18	206,0	124,0
20	254,0	154,0

CE 2.1 2.2 3.1 BL



- EN 12385-4
- DIN 3055
- završna obrada: el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm² ili 1960 N/mm²