

# 1. ČELIČNA UŽAD I LANCI Wire ropes and chains


## 1.2. Opća namjena

### Čelično uže: 6×19 + vlaknasta jezgra

#### Wire rope: 6x19 + FC

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm <sup>2</sup>	Min. prekidna sila (kN) 1960 N/mm <sup>2</sup>	Težina (kg/100 m)
Diameter	MBL	MBL	Weight
3	4,89	5,42	3,11
4	8,69	9,63	5,54
5	13,60	15,0	8,65
6	19,60	21,7	12,50
7	26,6	29,50	17,0
8	34,8	38,5	22,1
9	44,0	48,70	28,0
10	54,3	60,20	34,60
11	65,8	72,8	41,9
12	78,3	86,70	49,80
13	91,8	101,7	58,50
14	107,0	118,0	67,80
16	139,0	154,0	88,60
18	176,0	195,0	112,0
20	217,0	241,0	138,0
22	263,0	291,0	168,0
24	313,0	347,0	199,0
26	367,0	407,0	234,0
28	426,0	472,0	271,0
32	556,0	616,0	354,0
36	704,0	780,0	448,0
40	869,0	963,0	554,0




- EN 12385-4
- DIN 3060
- završna obrada: el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm<sup>2</sup> ili 1960 N/mm<sup>2</sup>

### Čelično uže: 6×19 + čelična jezgra

#### Wire rope: 6x19 + IWRC

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm <sup>2</sup>	Min. prekidna sila (kN) 1960 N/mm <sup>2</sup>	Težina (kg/100 m)
Diameter	MBL	MBL	Weight
3	5,77	6,39	3,43
4	10,30	11,4	6,1
5	16,0	17,7	9,53
6	23,1	25,5	13,7
7	34,4	34,8	18,7
8	41,0	45,4	24,4
9	51,9	57,5	30,90
10	64,1	71,10	38,1
11	77,5	85,90	46,1
12	92,3	102,2	54,9
13	108,3	119,90	64,4
14	126,0	139,0	74,7
16	164,0	182,0	97,5



- EN 12385-4
- DIN 3060
- završna obrada: el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm<sup>2</sup> ili 1960 N/mm<sup>2</sup>