

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.2. Opća namjena

Čelično užje: 6x37+ vlaknasta jezgra

Wire rope: 6x37 + FC

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1770 N/mm ²	Min. prekidna sila (kN) 1960 N/mm ²	Težina (kg/ m)
Diameter	MBL	MBL	Weight
5.00	13.1	14.5	0.085
6.00	18.8	20.8	0.125
7.00	25.6	28.3	0.170
8.00	33.4	37.0	0.221
9.00	42.3	46.8	0.280
10.00	52.2	57.8	0.346
11.00	63.1	70.0	0.419
12.00	75.1	83.3	0.498
13.00	88.2	97.7	0.585
14.00	102	113	0.678
15.00	118	131	0.782
16.00	134	148	0.886
17.00	152	168	1.003
18.00	169	187	1.120
19.00	189	209	1.250
20.00	209	231	1.38
21.00	231	256	1.52
22.00	253	280	1.67
23.00	277	307	1.83
24.00	301	333	1.99
25.00	327	362	2.16
26.00	353	391	2.34
27.00	381	422	2.52
28.00	409	453	2.71
30.00	472	523	3.12
32.00	534	591	3.54
34.00	605	670	4.01
35.00	641	710	4.24
36.00	676	749	4.48
38.00	756	837	5.01
40.00	835	925	5.54
42.00	923	1022	6.12
44.00	1010	1118	6.70
45.00	1058	1172	7.01
46.00	1105	1224	7.33
47.00	1153	1277	7.65
48.00	1200	1329	7.97
50.00	1305	1445	8.66
51.00	1358	1504	9.01
52.00	1410	1561	9.36
54.00	1525	1689	10.10
55.00	1583	1753	10.50
56.00	1640	1816	10.90
57.00	1700	1882	11.30
58.00	1760	1949	11.70
60.00	1880	2082	12.50



- EN 12385-4
- DIN 3066
- završna obrada: crno, el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1770 N/mm² ili 1960 N/mm²
- opća namjena, obično se koristi kod priveza i izrade čel. priveznica

